PAPER • OPEN ACCESS

The role of energy conservation standards in raising quality of life: Low- Cost Housing as a Case Study

To cite this article: Ayman A. Amin et al 2022 IOP Conf. Ser.: Earth Environ. Sci. 1056 012032

View the article online for updates and enhancements.

You may also like

- The Impacts of Building Contraventions and Informal Residential Land Subdivision on the Quality of Life in Baghdad A.S. Hajer Al Ishaqee and A. Enam Albazaz
- Evaluating the clinical benefit of braincomputer interfaces for control of a personal computer Adam Fry, Ho Wing Chan, Noam Y Harel et al.
- <u>Comparative carbon footprint analysis of</u> residents of wooden and non-wooden houses in Finland Juudit Ottelin, Ali Amiri, Bernhard Steubing et al.



244th Electrochemical Society Meeting

October 8 – 12, 2023 • Gothenburg, Sweden

50 symposia in electrochemistry & solid state science

Abstract submission deadline: **April 7, 2023**

Read the call for papers & **submit your abstract!**

This content was downloaded from IP address 156.187.241.64 on 04/03/2023 at 06:56

The role of energy conservation standards in raising quality of life: Low- Cost Housing as a Case Study

Ayman A. Amin¹, Noha M Ezz Eldin^{2, *}, Alshaimaa H. Mohammed³

¹ Department of Architecture, Faculty of Engineering, Banha University, Banha, Egypt

^{2,3} MTI University, Department of Architecture, Cairo, Egypt

*Corresponding Author Email: Nohaezz1@gmail.com

Abstract. Low-cost housing is spread all over Egypt from the north to the upper, many issues appeared on the horizon, such as high maintenance costs, high levels of energy consumption, and the emergence of many practices for residents of these units in an attempt to adapt between their needs and the design of low buildings. One of the most important challenges impacting the quality of life is energy conservation. This paper aims to raise the quality of life in low-cost housing from the perspective of energy conservation. The research aims to ensure enough sustainable energy to maintain a quality of life. This study is based on questionnaires conducted by residents of low-cost houses projects in Egypt, namely; Mokattem and New Cairo. Trying to find the most important problem and put forward ways to improve and raise the quality of life, especially from the perspective of energy conservation. Studying the Living satisfaction in low- cost houses. These questionnaires were analysed on a proposal design and how to apply it.

Keywords: Low-cost housing, Energy conservation, Quality of life (QOL).

1. Introduction

Over the last few years the Egyptian government has pay attention to the approach of the low-cost housing .This is becoming an issue of great importance recently as a most suitable way to obtain decent housing Compatible with the economic conditions of Egyptian society [1]. Providing a suitable residential environment is considered one of the critical challenges government encounters especially since 52% of the population is with average income. The interest of the government is shown through the number of low-cost buildings in Fig no. (1) which represents that the number of low-cost units and economic housing alone is about 84,981 during the period 2019-2020. In light of this, Understanding quality of life is a key measurement for cities' liveability and habitability [14], especially for Low -cost housing.



Figure 1. Number of low-cost housing units built by Egyptian government according to Central Agency for Mobilization and Statistics Issue: July 2021.

Content from this work may be used under the terms of the Creative Commons Attribution 3.0 licence. Any further distribution of this work must maintain attribution to the author(s) and the title of the work, journal citation and DOI. Published under licence by IOP Publishing Ltd 1

International Conference on Civil and Architecture En	IOP Publishing	
IOP Conf. Series: Earth and Environmental Science	1056 (2022) 012032	doi:10.1088/1755-1315/1056/1/012032

2. Quality of Life

The expression "quality of life" (QOL) applies toward an assessment made regarding important components of a human's life or society [3]. It can be categorized as individual (physical and psychological health), interpersonal (social relationships), and -contextual (environment) aspects. It can also be could described by them or determined by 'physical indicators [4]. QOL has been determined as an interaction of social, health, economic and environmental conditions that have an impact on the development of the individual and society [5]. It is important to understand the impact of QOL on sustainable development [6].

2.1 Energy conservation QOL indicators for low -cost QOL housing

Several studies have explored the effects of energy consumption on **QOL** and human development (Index HDI) [7].Recent QOL indicators have started to focus on low-cost housing evaluation [9], the research adopted appropriate and important indicators in energy conservation. A suitable set of indicators to measure quality of low-cost housing should provide relevant data on both the physical indicators of a residence [8], as well as the inside environment which includes fundamental services. For instance well-designed housing has been identified as an important factor in promoting quality of life, orientation, internal spaces, electricity, water system, indoor running water, bathroom standards, and cooking facilities. These indicators were designed according to Sustainable Development Goals (SDGs) [10]. Neighborhood aspects are represented in the surrounding environment, level of noise, the quality of transportation services, etc. Monthly income is an essential signal of satisfaction in the household realm [11].The following table adapts several indicators of QOL according to the related items for energy conservation.

2.1.1 Parameters regarding energy saving:

More than 70% of the total energy consumed in residential buildings is attributed to lighting and HVAC (heating, ventilation and air conditioning) needs. Energy-saving parameters in Low-cost housing play a role in dictating the energy efficiencies and are liable for energy-saving programs.

2.1.2 Parameters regarding energy production:

Access to energy is a key pillar for human wellbeing [15]. Our ultimate goal is to ensure that everyone has access to enough sustainable energy to maintain a high standard of living. For energy production, the study has obtained several indictors related to energy conservations on a scale inside and outside the low-cost housing.

		Indicator	Determinant purpose		
-	Building Mass	Building mass has an impact on day	Preserving open space through housing clusters,		
		lighting, quality and hence energy	housing units are built close together on a large		
		consumption. Housing units are built	lot, with the rest of the lot left as common open		
		close together on a large lot.	space. Each unit has a small open space.		
E Building It is important to consider the actual quantity of solar radiation on the facades of a r			ity of solar radiation on the facades of a residential		
Sig	Orientation	entation unit ,as it affects the thermal load of the residential unit and controls the thermal behavior			
De		and the amount of thermal comfort of the	space.		
ing	Optimal space	The prorate area of the house important	for lower risk of respiratory infections. Optimal		
standard and circulation Building Building Standard and circulation Building Standard and circulation Building Standard and Building Standard and Standard and St			ealth. Poverty is improved access to key services		
			erior environment from less desirable exterior		
	Envelope conditions. It is an important aspect in determining how much energy will be needed to				
heat or cool, light and ventilates the building.					
Building The differences in shape between the buildings were found to have a large impa			ldings were found to have a large impact [2] and		
	Shape	rgy demand [3].			

 Table 1: QOL indictors for energy conservation.

International Conference on Civil and Architecture En	gineering (ICCAE-14)	IOP Publishing
IOP Conf. Series: Earth and Environmental Science	1056 (2022) 012032	doi:10.1088/1755-1315/1056/1/012032

Openings	The most important factors regarding openings include the amount of sunshine that enters a room, the view, and human privacy. The best window room can vary. The favorite direction to the air movement path and the position of the openings completely permeates the vacuum.	
Sustainable construction materials	The use of less carbon-intensive Matural ecosystem protection limiting materials (e.g. cement, steel) or materials that store carbon (e.g. wood). These could [4] support de-carbonization of the industry sector, hence less need for energy-intensive resource extraction.	
conservation of natural resources	The Water management system can be achieved by energy recovery, and conserving and reusing water using low-flow faucets.	
Green Space	The ratio of land consumption to the population growth.	
Factor.	A well-insulated roof can negate the need for mechanical systems and reduce heating, cooling needs. Green roofs can reduce storm water volumes by up to 85%	
~	and the ceiling temperature, [5].	
Spreading bike and car roads	Creating pedestrian- and bike-friendly spaces and walking/running paths, etc. to encourage exercise and discourage unnecessary driving.	

3. Analytical Study

The study relies on two main factors the first is through a survey of visiting social low – cost housing models in Cairo (Mokattam- New Cairo) and observation the changes made by the residents to achieve their needs Fig (1,2,3), which the Egyptian government designed and implemented during the past ten years. For energy conservation we must study smart finishing to produce energy on landscape and public buildings as shown in table (3).

Figure 2. Changing the area and	Figure 3. Using temporary	Figure 4. Narrow spaces
the shape of windows by closing	curtain to cover balconies	between buildings to obtain
or increasing the window space.	workplaces under buildings.	maximum privacy.
Ref. Take by Author	Ref. Take by Author	Ref. Take by Author

4. Questionnaire results

The data used in the study was obtained from a questionnaire given to low - cost housing residents. Factors that may influence the study are quality of life and housing environment satisfaction (physical Aspects). The questionnaire was published on websites and distributed to low-income housing residents to study the problems of raising the quality of life through the concept of energy conservation.

The results were analysed by the SPSS program to obtain the percentage, mean, St Deviation of the results which is a essential elements in the design proposal.



Figure 5. The value of the above-described approach is questionable for stratifying the residents on low- cost house location for public services found that 46% was closed and narrow to public services.



Figure 7. For the orientation of widows the results found it suitable for natural 34% was think it was not suitable and not suitable very enough and 56% was staffing to windows orientation.



Figure 9. For The internal spaces inside the unit disposed of it was found that 53% thought it was suitable for them and 47% have thought it was not suitable.



Figure 6. Housing units are built close together found that it was 43% for good spaces between the building and 21% for much closed spaces between the building.



Figure 8. For natural lighting and the widows area found that 49% thought that it was very suitable and suitable for natural lighting 51% thought it was not suitable enough.



Figure 10. For the suitable methods to dispose of construction waste properly 75% of them are suitable.

IOP Conf. Series: Earth and Environmental Science





Figure 11. For the range of monthly electric bill 30% mentioned that it was 400-600 L.E. It is so high compared to their income .45% between 200-400 L.E and it is considered high according to low-cost housing.

Figure 12. For conserving and reusing rainwater 80% represents that there is no method for conserving rain.

5. Result and Discussion:

The analytical study was based on result in the previous questionnaire, which showed varying rates in satisfaction on the design and rates of energy saving and comfort within spaces, Based on the results, we make the following observations:

1056 (2022) 012032

5.1. Building design

- Building Mass :Separating Housing units Preserving open space through housing clusters
- **Building Orientation:** The unit should take 3 different directions at less In order to improve the rates of lighting and thermal comfort.
- **Building Shape:** The use of the Square shape in spaces design Preserving open space through housing clusters.
- **Optimal space standard and circulation:** Taking into account the proportions in the design spaces significantly contributed to the reducing waste area in spaces and be more accommodate future needs.
- **Openings**: There must be windows in every space regard the favorite direction and air movement path, Fig. 13.



ABRIR Too92

Figure 13. Designing the windows in different orientation allowing good air movement path.

Figure 14. The current situation in low cost housing windows was designed in one orientation.

5

IOP Publishing

doi:10.1088/1755-1315/1056/1/012032

5.2. Urban and energy production

Regarding energy production in QOL indicators for Low -cost housing some important strategies are presented to achieve the production of energy:

- Conservation of natural resources: Water management system can be achieved by energy recovery, and conserving and reusing water. Using low-flow faucets.
- Green Space Factor: Raising the rate of green elements in Law cost housing urban spaces, encourage people to use Green roofs techniques which can reduce storm water volumes by up to 85% and the ceiling temperature.
- Spreading bike and car roads Creating pedestrian- and bike-friendly spaces and walking/running paths.
- Sustainable construction materials:
 - Roads with Solar Panels: It is a new technique that combines environmental corridors and lighting together with lighting path instead of traditional lighting poles.
 - Artificial wind tree: Wind tree is used for the generation of energy from wind the leaves act as mini wind turbines which are capable of providing power.
 - Solar PV Parking Structure: putting Parking Lot Solar PV, By power shading structure we are not only able to make more use of the land Parking lot solar
 - Wind and solar powered hybrid street lamp: It can transfer solar and wind power to electric power and incorporates Stable operation, non-cable working, No conventional energy consumption, long life span.
 - Tilfs for energy production: It converts the kinetic energy into electric energy and is stored in the units under the title to be used in various activities inside the building. One step produces 5-7 watts.
 - Photovoltaic cells: The building's facades and surfaces are supported by photovoltaic units to transform solar energy into electrical energy and can be placed on the hospital buildings in a decent manner providing aesthetic areas.

6. Applied Study

Designing the units may have been the main factor explaining the rising of consuming energy its related to some more factors (Building Mass- Building Orientation- Building Envelope- Building Shape) From that the research suggest an Architectural proposal design plan of a low-cost housing regarding energy and economic issues.



Figure 15. The current area is 90 m^2 and orientation is 2 different directions at maximum.

IOP Conf. Series: Earth and Environmental Science

1056 (2022) 012032

doi:10.1088/1755-1315/1056/1/012032



Figure 16. Design proposal for the $70m^2$ separating the building mass –regarding the orientation for every unit – avoiding the cross-sections in circulation.



Figure 17. Design proposal for the $90m^2$ separating the building mass –regarding the orientation for every unit – avoiding the cross-sections in internal circulation.

7. Conclusions

The analytical study focused on assessing and analysing the questionnaire and suggesting the necessary .modifications to solve the previously mentioned problems through the evaluation of rationalization and production of energy in terms of different items as introduced in a table.

The quality-of-life indicators were studied in terms of (energy rationalization and production). Conducting a questionnaire that measures the extent to which these criteria are applied, as low housing costs by the resident population. These indicators were analysed to make a redesign of the current situation of low-cost housing. The research proposed a housing unit of minimum surface area for one room not less than $3.3m^2$. Attention to the direction of the openings of the doors, and considering the shape of the square-shaped unit. Orientation per unit to 3 directions instead of 2 directions, and considering privacy.

8. Recommendations

- 1) Applying the indicators of energy conservation by taking into account the design standards, both internally and externally in Low -cost housing.
- 2) The smart technique should be focused on the start of planning instead of treatment, and it is not considered expensive if it is compared to with the executed quantity and the time element.
- 3) The possibility of transforming existing Low -cost housing to energy producers building through the cultivation of solar cell surfaces, the use of wind and solar-powered hybrid street lamps, solar-powered glass, energy-producing floors and landscape can be easily achieved from the preliminary stages of design as shown in the proposed design.
- 4) The researchers recommend the application of energy-producing technologies in there various forms inside public buildings attached to low-cost housing to security aspects of maintenance work and to produce energy to reduce expenditures on the citizen's priest.

References

- [1] Al-Qawasmi, J. (2020). "Measuring Quality of Life in Urban Areas: Toward an Integrated Approach." Int. J. Environ. Sci. Nat. Resour 25: 67-74.
- [2] Fassio, O., C. Rollero, and N. De Piccoli, *Health, quality of life and population density: A preliminary study* on "contextualized" quality of life. Social indicators research, 2013. **110**(2): p. 479-488

International Conference on Civil and Architecture Engineering (ICCAE-14)		IOP Publishing
IOP Conf. Series: Earth and Environmental Science	1056 (2022) 012032	doi:10.1088/1755-1315/1056/1/012032

- [3] Co-operation, O. f. E. and Development (2019). Accelerating Climate Action: Refocusing Policies through a Well-being Lens, OECD Publishing.
- [4] Cutter, S. L. (1985). Rating places: A geographer's view on quality of life, Assn of Amer Geographers.
- [5] Danielski, I., M. Fröling and A. Joelsson (2012). The impact of the shape factor on final energy demand in residential buildings in nordic climates. World Renewable Energy Forum, WREF 2012, Including World Renewable Energy Congress XII and Colorado Renewable Energy Society (CRES) Annual Conference; Denver, CO; 13 May 2012through17 May 2012; Code94564.
- [6] Del Pero, A. S., W. Adema, V. Ferraro and V. Frey (2016). "Policies to promote access to good-quality affordable housing in OECD countries."
- [7] Gasper, D. (2010). "Understanding the diversity of conceptions of well-being and quality of life." The Journal of Socioeconomics 39(3): 351-360.
- [8] IEA, G. E. (2019). "CO2 Status Report 2018." International Energy Agency, Paris 562.
- [9] Karim, H. A. (2012). "Low cost housing environment: compromising quality of life?" Procedia-Social and Behavioural Sciences 35: 44-53.
- [10] Muhammad, S. and A. Sabo, (2021) "The Impact of Energy and Electricity Consumption on Quality of Life in Africa." Research Journal of Business Management 4(1):104-109
- [11] Robinson-Smith, G., M. V. Johnston and J. Allen (2000). "Self-care self-efficacy, quality of life, and depression after stroke." Archives of physical medicine and rehabilitation 81(4): 460.
- [12] Sapkota, J. B. (2014). "Access to infrastructure and human development: Cross-country evidence." Perspectives on the Post-2015 Development Agenda. Tokyo: JICA Research Institute.
- [13] Stamenković, M. G., M. J. Miletić, S. M. Kosanović, G. D. Vučković and S. M. Glišović (2018). "Impact of a building shape factor on space cooling energy performance in the green roof concept implementation." Thermal Science 22(1 Part B): 687-698.
- [14] Group, T.W., The World Health Organization quality of life assessment (WHOQOL): development and general psychometric properties. Social science & medicine, 1998. 46(12): p. 1569-1585.
- [15] Vijayaraghavan, K. (2016). "Green roofs: A critical review on the role of components, benefits, limitations and trends." Renewable and sustainable energy reviews 57: 740-752.
- [16] Mohamed, Noha, Criteria to Evaluate Energy Saving and Production in Hospitals "Nursing Units", PHD thesis, Architectural Engineering, Faculty of Engineering, Cairo University, Giza, Egypt, 2019.