
Contents lists available at ScienceDirect



Energy Conversion and Management



journal homepage: www.elsevier.com/locate/enconman

Study of Egyptian castor biodiesel-diesel fuel properties and diesel engine performance for a wide range of blending ratios and operating conditions for the sake of the optimal blending ratio



Ali M.A. Attia^{a,b}, Mohamed Nour^b, S.A. Nada^{b,c,*}

^a Mechanical Engineering Department, College of Engineering, University of Bisha, Bisha, Saudi Arabia

^b Mechanical Engineering Department, Faculty of Engineering, Banha University, Benha, Egypt

^c Egypt-Japan University of Science and Technology, New Borg El-Arab City, Alexandria, Egypt

ARTICLE INFO

Keywords: Castor biodiesel Diesel engine performance Emission characteristics ISO 8178

ABSTRACT

Egyptian Castor raw oil has been used to produce Castor Methyl Ester (CME) biodiesel utilizing Transesterification-ultrasonic process. To meet the ASTM requirements, CME was blended with the conventional diesel fuel for improving sooting tendency and fuel viscosity. Thermal analysis showed that CME has comparable end-boiling temperature and fuel-air mixing of the diesel fuel. Experiments on a single-cylinder engine in accordance to G-2 of ISO 8718 standard were conducted at wide ranges of blending ratios and operating conditions. Comparing to the neat diesel fuel data, the results of testing CME biodiesel fuel showed that (i) a maximum increase of 8% in the brake specific energy consumptions was received at a blending ratio of 30%, (ii) a slight increase in the brake thermal efficiency (around 1%) was obtained at a blending ratio of 20%, (iii) the best reduction in the carbon monoxide emission (CO), unburned hydrocarbons (HC), nitrogen oxides (NOx) were 17%, 40%, and 0.05%, respectively as recorded at a blending ratio of 10%, (iv) the best reduction of 7.5% in carbon dioxide emissions was observed at 20% blending ratio, and (v) the minimum opacity level was observed at a blending ratio of 30%. The results conclude that the 20% blending ratio is recommended to keep high engine efficiency without environmental deterioration.

1. Introduction

Fuel consumption in the transportation sector increases annually with a rate of 1.4%. Diesel fuel has the highest consumption compared to the other fuels as shown in Fig. 1 [1]. The fossil fuel depletion problem is currently facing all the countries of the world. It is necessary to find alternatives non-fossil fuels for the transportation sector. In the recent decades, there was a great attention to use biofuels as an effective alternative of the diesel fuel [2]. The advantages of biodiesels to be used as alternative fuel are the null impact on the greenhouse phenomena, lower emissions due to existing of oxygen compound in fuel structure, biodegradable...etc. [3,4]. Biodiesel is usually prepared from fatty acids (FA) in vegetable oils and animal fats by reacting them with alcohols catalyzed using acid/base catalyst. The feedstock of vegetable oils may be edible oils (first generation) or non-edible oils (second generation). Recently, non-edible feedstock seems to be more attractive for biodiesel production to overcome on any crisis related to food production [5].

In Egyptian territory, there are many suitable non-edible feedstocks that possess high oil contents in their seeds; such as Jatropha, Jojoba, Palm seed, Castor, and others. The biodiesel production cost depends mainly on the cost of the raw oil (around 75% of cost is paid to get the raw oil) [6]. Using low-priced feedstock, the biodiesel production cost may be reduced and approached that of the petrol diesel fuel [7,8]. After reviewing the prices of the non-edible oils in Egypt, it was found that the price of Castor oil is the cheapest one, then Jatropha, while Jojoba has the highest price. Considering the high availability and the low cost of castor raw oil in Egypt, it is attractive to check its viability to produce biodiesel and to examine its effect on the diesel engines performance.

Castor plants (*Ricinus Communis* L.) can be cultivated in marginal lands with low water demands. Seeds of castor need four months for harvesting with relatively high oil contents (around 50% by weight). The chemical structure of the castor raw oil possesses three chemical groups; carboxyl, hydroxyl and carbon-carbon double bond. Castor oil is suitable for industrial applications rather than food applications

https://doi.org/10.1016/j.enconman.2018.08.016

^{*} Corresponding author at: Mechanical Engineering Department, Faculty of Engineering, Banha University, Benha, Egypt. *E-mail address:* sameh.nada@ejust.edu.eg (S.A. Nada).

Received 11 May 2018; Received in revised form 14 July 2018; Accepted 5 August 2018 0196-8904/ © 2018 Elsevier Ltd. All rights reserved.